

Heating Cabinets WS

Medical Device Class I

Intended Use

Type F: Tempering of fango packs in physiotherapy

Type S/SE: Heating and tempering of silicate packs in physiotherapy

Equipment

- Self-supporting housing made of stainless steel with structured surface
- Inner housing with 6 or 14 insertion slots
- Standard equipment
 - WS 6-6044 F and WS 6-7054 F - 5 aluminium fango trays
 - WS 14-6044 F and WS 14-7054 F - 10 aluminium fango trays
 - WS 6-6044 S / SE and WS 6-7054 S / SE - 4 perforated aluminium trays
 - WS 14-6044 S / SE and WS 14-7054 S / SE - 10 perforated aluminium trays
- Insulated front door with magnetic lock and red, green or black coloured handle bars
- Electronic temperature control from 30 °C to 85 °C (heating cabinets F) or 30 °C to 95 °C (heating cabinets S / SE)
- Control accuracy ± 2 °C
- Consistent and fast heating due to air circulation system
- Power On indicator lamp
- Heating indicator lamp



Optional Accessories

Mobile steel rack, consisting of

- Powder coated steel frame
- Four castor rolls (two of which are lockable)
- Four support points for the water bath
- Stainless steel storage shelf



Storing unit, consisting of

- Powder coated steel frame with housing made of stainless steel with structured surface
- Four castor rolls (two of which are lockable)
- 12 insertion slots



Technical Data

Device Article Number	Insertion Slots	Heating Capacity (W)	Nominal Voltage (V)	Outer Dimensions (mm) L x T x H	Temperature Range
WS 6-6044 F 0030.006	6	1000	230	685 x 641 x 505	30 °C - 85 °C
WS 14-6044 F 0030.014	14	1000	230	685 x 641 x 800	30 °C - 85 °C
WS 6-7054 F 0037.006	6	1000	230	785 x 732 x 505	30 °C - 85 °C
WS 14-7054 F 0031.014	14	1000	230	785 x 732 x 800	30 °C - 85 °C
WS 6-6044 S 0030.106	6	1000	230	685 x 641 x 505	30 °C - 95 °C
WS 14-6044 S 0030.114	14	1000	230	685 x 641 x 800	30 °C - 95 °C
WS 6-7054 S 0037.106	6	1000	230	785 x 732 x 505	30 °C - 95 °C
WS 14-7054 S 0031.114	14	1000	230	785 x 732 x 800	30 °C - 95 °C
WS 6-6044 SE 0030.206	6	2000	230	685 x 641 x 505	30 °C - 95 °C
WS 14-6044 SE 0030.214	14	2000	230	685 x 641 x 800	30 °C - 95 °C
WS 6-7054 SE 0037.206	6	2000	230	785 x 732 x 505	30 °C - 95 °C
WS 14-7054 SE 0031.214	14	2000	230	785 x 732 x 800	30 °C - 95 °C

All dimensions are given in SI units